

Page **1** of **7** –

1

2

## Lyden Fuel Force Synthetic P/S Fluid & Conditioner

#### SDS Number: FF335

#### PRODUCT AND COMPANY INFORMATION

| Product Name:    | Lyden Fuel Force Synthetic P/S Fluid & Conditioner |
|------------------|--|
| Revision Date:   | 03/06/2025   |
| SDS Number:      | FF335  |
| Common Name:     | Hydrotreated heavy paraffinic power steering fluid |
| CAS Number:      | Blend  |
| Product Code:    | FF335  |
| <u>Synonyms:</u> | Power Steering Fluid                               |

#### **Company Identification:**

| Manufactured for:   |  |
|---------------------|--|
| LYDEN OIL COMPANY   |  |
| 30692 Tracy Rd.     |  |
| Walbridge, OH 43462 |  |
| www.lydenoil.com    |  |

| For Product Information: | 1-800-245-9336            |
|--------------------------|---------------------------|
| For Emergencies:         | 1-800-424-9300 (CHEMTREC) |

#### HAZARDS IDENTIFICATION

| Signal Word:                    | None   |
|---------------------------------|--|
| Hazard Classes/Categories:      | None   |
| Hazard Statement(s):            | None   |
| <u>Precaution Statement(s):</u> | P101: If medical advice is needed, have product container or label at<br>hand.<br>P102: Keep out of reach of children.<br>P103: Read label before use. |



Page 2 of 7 -

Lyden Fuel Force Synthetic P/S Fluid & Conditioner

SDS Number: FF335

Other Hazard Statement(s):

-NFPA Ratings: Health = 0 Fire = 1 Reactivity = 0

#### **COMPOSITION / INFORMATION ON INGREDIENTS**

Ingredients:

3

Mixture of the substances listed below with nonhazardous additions.

| Chemical Name  | CAS Number | Percentage |
|--|------------|------------|
| Distillates (petroleum), hydrotreated heavy paraffinic | 64742-54-7 | 60-100     |

\*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

| 4 FIRST AID WEASORES |
|----------------------|
|----------------------|

#### **Description of First Aid Measures:**

| Inhalation:   | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.   |
|---------------|---|
| Skin Contact: | Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.  |
| Eye Contact:  | Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Get medical attention if irritation occurs.  |
| Ingestion:    | Wash out mouth with water. Remove victim to fresh air and keep at<br>rest in a position comfortable for breathing. If material has been<br>swallowed and the exposed person is conscious, give small quantities<br>of water to drink. Do not induce vomiting unless directed to do so by<br>medical personnel. Get medical attention if symptoms occur. |



Page **3** of **7** –

6

# Lyden Fuel Force Synthetic P/S Fluid & Conditioner

Symptoms and Effects, both acute and delayed:

No further relevent data available.

**Recommended Actions:** 

SDS Number: FF335

Treat symptomatically. Call a doctor or poison control center for guidance.

| 5                    | FIRE FIGHTING MEASURES        |   |
|----------------------|-------------------------------|---|
| <u>Recommended F</u> | Fire-Extinguishing Equipment: | Use dry powder, foam, or carbon dioxide fire<br>extinguishers. Water may be ineffective in fighting<br>an oil fire unless used by experienced fire fighters.                                      |
| Possible Hazards     | <u>S During a Fire:</u>       | Hazardous combustion products may include: A<br>complex mixture of airborne solid and liquid<br>particulates and gases (smoke). Carbon monoxide.<br>Unidentified organic and inorganic compounds. |
| <u>Recommendatio</u> | ns to Firefighters:           | Proper protective equipment including breathing apparatus.  |

#### ACCIDENTAL RELEASE MEASURES

| Personal Precautions: |  |
|-----------------------|--|
|                       | Avoid eye contact. Avoid repeated or prolonged skin contact.                   |
|                       | Personal protective equipment must be worn.                                    |
|                       | Avoid contact with skin, eyes or clothing.                                     |
| Emergency Procedures: |  |
|                       | Contain spilled material, collect in suitable and properly labeled containers. |



Page 4 of 7 -

## **Safety Data Sheet**

| C                            | Lyden Fuel Force Synthetic P/S Fluid & Conditioner   |
|------------------------------|--|
| SDS Number: FF335            |  |
| Environmental Precautions:   |  |
|                              | Do not allow product to reach sewage system or<br>any water course.<br>Inform respective authorities in case of seepage<br>into water course or sewage system.   |
| <u>Cleanup Procedures:</u>   | Absorb with liquid-binding material (sand,<br>diatomite, acid binders, universal binders, sawdust).<br>Ensure adequate ventilation.  |
| 7 HANDLING AND STORA         | IGE  |
| Handling Precautions:        | Wear personal protective equipment. Avoid contact with eyes.   |
| <u>Storage Requirements:</u> | Store in accordance with local regulations. Store in<br>original container protected from direct sunlight in<br>a dry, cool and well-ventilated area, away from<br>incompatible materials and food and drink. Keep<br>container tightly closed and sealed until ready for<br>use. Containers that have been opened must be<br>carefully resealed and kept upright to prevent<br>leakage. Do not store in unlabeled containers. Use<br>appropriate containment to avoid environmental<br>contamination. |

#### 8

**EXPOSURE CONTROLS / PERSONAL PROTECTION** 

#### Exposure Limits:

-64742-54-7 Distillates (petroleum), hydrotreated heavy parffinic (60-100%):

ACGIH TWA – 5mg/m<sup>3</sup> (oil mist) ACGIH STEL - 10mg/m<sup>3</sup> (oil mist) OSHA TWA – 5mg/m<sup>3</sup> (oil mist)

#### Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).



Page **5** of **7** –

## Lyden Fuel Force Synthetic P/S Fluid & Conditioner

SDS Number: FF335

Personal Protective Equipment:

Wash hands before breaks and at the end of work. Use safety glasses and gloves.

9

#### PHYSICAL AND CHEMICAL PROPERTIES

| Color:                     | Clear   |
|----------------------------|---|
| Physical State:            | Liquid  |
| Odor:                      | Petroleum                                     |
| Odor Threshold:            | Data not available                            |
| pH:                        | Data not available                            |
| Melting Point:             | Data not available                            |
| Boiling Point:             | Data not available                            |
| Boiling Range:             | Data not available                            |
| Flash Point:               | >200° C / >392° F (COC Method)                |
| Evaporation Rate:          | Data not available                            |
| Flammability:              | Data not available                            |
| Flammability Limits:       | Data not available                            |
| Vapor Pressure:            | Data not available                            |
| Vapor Density:             | Data not available                            |
| Relative Density:          | 0.84 to 0.865                                 |
| Solubilities:              | Insoluble in water                            |
| Partition Coefficient:     | Data not available                            |
| Auto-Ignition Temperature: | Data not available                            |
| Decomposition Temperature: | Data not available                            |
| Viscosity:                 | >25 mm <sup>2</sup> /sec (kinematic at 40° C) |
|                            |   |

# 10 STABILITY AND REACTIVITY Stability: Stable under normal conditions. Reactivity: Not reactive under normal conditions. Conditions to Avoid: No further relevant information available. Hazardous Reactions: No known hazardous reactions.



Page 6 of 7 -

## **Safety Data Sheet**

|                                     | Ludon Fuel Force Sunthatic D/S Eluid & Conditioner  |
|-------------------------------------|---|
| SDS Number: FF335                   | Lyden Fuel Force Synthetic P/S Fluid & Conditioner  |
| Incompatible Materials:             | Strong oxidizers.   |
| Decomposition Products:             | Oxides of carbon.   |
| 11 TOXICOLOGICAL INFORM             | MATION  |
| Routes of Exposure:                 | Inhalation, skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion. |
| Exposure Effects:                   | Repeated skin contact may cause dermatitis or an oil acne.  |
| Measures of Toxicity:               | No test data available.   |
| Carcinogenic/Mutagenic Precautions: | Non-carcinogenic and not expected to be mutagentic.   |

#### **ECOLOGICAL INFORMATION**

#### **Ecological Precautions:**

Do not allow product to reach ground water, water course or sewage system.

#### **Ecological Effects:**

12

13

No specific environmental or aquatic data available.

#### DISPOSAL CONSIDERATIONS

#### **Disposal Methods:**

Dispose of waste material in accordance with all local, state, and federal requirements.



Page 7 of 7 -

# **Safety Data Sheet**

|   |                        | Lyd  | en Fuel Force Synthetic P/S Fluid & C         | onditioner |
|---|------------------------|--|---|------------|
| SDS Number: FF  | 335                    |  |   |            |
| Disposal Contair  | ners:                  |  | Use properly approved container for disposal. |            |
| <u>Special Precauti</u>   | <u>ons:</u>            |  | Do not flush to surface waters or drains.     |            |
| 14  | <b>TRANSPORT</b>       | NFORMATION   |   |            |
| <u>UN Number:</u><br><u>UN Shipping Nat</u><br><u>Transport Hazar</u><br>Packing Group: | <u>me:</u><br>d Class: | Data not available<br>Data not available<br>Data not available<br>Data not available |   |            |
| Environmental H   | lazards:               |  | Data not available                            |            |
| Bulk Transport (  | <u>Guidance:</u>       |  | Data not available                            |            |
| Special Precauti  | <u>ons:</u>            |  | Not regulated by DOT.                         |            |
| 15  | REGULATORY INFORMATION |  |   |            |

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

| 16 | OTHER INFORMATION |
|----|-------------------|

#### Last Revision Date: 03/06/2025

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. The supplier assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the supplier.



Page **1** of **8** –

1

## Lyden Fuel Force Power Steering Flush

#### SDS Number: FF350

#### PRODUCT AND COMPANY INFORMATION

| Product Name:    | Lyden Fuel Force Power Steering Flush              |
|------------------|--|
| Revision Date:   | 03/06/2025   |
| SDS Number:      | FF350  |
| Common Name:     | Hydrotreated heavy paraffinic power steering flush |
| CAS Number:      | Blend  |
| Product Code:    | FF350  |
| <u>Synonyms:</u> | Power Steering Flush                               |

#### **Company Identification:**

Manufactured for: LYDEN OIL COMPANY 30692 Tracy Rd. Walbridge, OH 43462 www.lydenoil.com

| For Product Information: | 1-800-245-9336            |
|--------------------------|---------------------------|
| For Emergencies:         | 1-800-424-9300 (CHEMTREC) |

#### HAZARDS IDENTIFICATION



Signal Word:

2

Hazard Classes/Categories:

DANGER

Aspiration hazard, Category 1.

Hazard Statement(s):

H304: May be fatal if swallowed and enters airways.



#### Page 2 of 8 -

## Lyden Fuel Force Power Steering Flush

#### SDS Number: FF350

#### Precaution Statement(s):

P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P103: Read label before use.
P301+310: IF SWALLOWED: Immediately call a POISON
CENTER/doctor
P331: Do NOT induce vomiting.
P405: Store locked up.
P501: Dispose of contents/container in accordance with local/regional/national/international regulation.

#### Other Hazard Statement(s):

-NFPA Ratings: Health = 0 Fire = 1 Reactivity = 0

#### **COMPOSITION / INFORMATION ON INGREDIENTS**

#### Ingredients:

3

Mixture of the substances listed below with nonhazardous additions.

| Chemical Name  | CAS Number | Percentage |
|--|------------|------------|
| Distillates (petroleum), hydrotreated heavy paraffinic | 64742-54-7 | 60-100     |
| White mineral oil (petroleum)                          | 8042-47-5  | 1-5        |

\*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

#### 4 FIRST AID MEASURES

#### Description of First Aid Measures:

Inhalation:

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately.



#### Page 3 of 8 -

SDS Number: FF350

## Lyden Fuel Force Power Steering Flush

| Skin Contact:                  | •   | and water. Remove contaminated clothing and wash<br>et medical attention if needed.   |
|--------------------------------|---|---|
| Eye Contact:                   | Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Get medical attention if irritation occurs.  |   |
| Ingestion:                     | Get medical attention immediately. Call a poison center or physician.<br>Wash out mouth with water. Remove victim to fresh air and keep at<br>rest in a position comfortable for breathing. If material has been<br>swallowed and the exposed person is conscious, give small quantities<br>of water to drink. Stop if the exposed person feels sick as vomiting<br>may be dangerous. Aspiration hazard if swallowed. Can enter lungs<br>and cause damage. Do not induce vomiting. Never give anything by<br>mouth to an unconscious person. If unconscious, place in recovery<br>position and get medical attention immediately. |   |
| Symptoms and Effects, both a   | cute and delayed:   | Ingestion: Adverse symptoms may include the following: nausea or vomiting.  |
| Recommended Actions:           |   | Treat symptomatically. Call a doctor or poison control center for guidance.   |
| 5 FIRE FIGHT                   | NG MEASURES   |   |
| Recommended Fire-Extinguish    | ning Equipment:   | Use dry powder, foam, or carbon dioxide fire<br>extinguishers. Water may be ineffective in fighting<br>an oil fire unless used by experienced fire fighters.                                      |
| Possible Hazards During a Fire | <u>:</u>  | Hazardous combustion products may include: A<br>complex mixture of airborne solid and liquid<br>particulates and gases (smoke). Carbon monoxide.<br>Unidentified organic and inorganic compounds. |



Page **4** of **8** –

## Lyden Fuel Force Power Steering Flush

SDS Number: FF350

**Recommendations to Firefighters:** 

Proper protective equipment including breathing apparatus.

| 6 ACCIDENTAL RELEASE MEASU | ACCIDENTAL RELEASE MEASURES  |  |  |
|----------------------------|--|--|--|
| Personal Precautions:      |  |  |  |
|                            | Avoid eye contact. Avoid repeated or prolonged skin contact.   |  |  |
|                            | Personal protective equipment must be worn.<br>Avoid contact with skin, eyes or clothing.  |  |  |
| Emergency Procedures:      |  |  |  |
|                            | Contain spilled material, collect in suitable and properly labeled containers.   |  |  |
| Environmental Precautions: |  |  |  |
|                            | Do not allow product to reach sewage system or<br>any water course.  |  |  |
|                            | Inform respective authorities in case of seepage   |  |  |
|                            | into water course or sewage system.  |  |  |
| Cleanup Procedures:        | Absorb with liquid-binding material (sand,   |  |  |
|                            | diatomite, acid binders, universal binders, sawdust).<br>Ensure adequate ventilation.  |  |  |
| 7 HANDLING AND STORAGE     |  |  |  |
| Handling Precautions:      |  |  |  |
|                            | Wear personal protective equipment. Avoid contact with eyes.   |  |  |
| Storage Requirements:      |  |  |  |
|                            | Store in accordance with local regulations. Store in<br>original container protected from direct sunlight in<br>a dry, cool and well-ventilated area, away from<br>incompatible materials and food and drink. Keep<br>container tightly closed and sealed until ready for<br>use. Containers that have been opened must be |  |  |



Page **5** of **8** –

SDS Number: FF350

### Lyden Fuel Force Power Steering Flush

carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

#### **EXPOSURE CONTROLS / PERSONAL PROTECTION**

#### Exposure Limits:

8

-64742-54-7 Distillates (petroleum), hydrotreated heavy parffinic (60-100%):

ACGIH TWA – 5mg/m<sup>3</sup> (oil mist) ACGIH STEL - 10mg/m<sup>3</sup> (oil mist) OSHA TWA – 5mg/m<sup>3</sup> (oil mist)

#### Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work. Use safety glasses and gloves.

#### 9

#### PHYSICAL AND CHEMICAL PROPERTIES

| Color:               | Clear                          |
|----------------------|--------------------------------|
| Physical State:      | Liquid                         |
| Odor:                | Petroleum                      |
| Odor Threshold:      | Data not available             |
| pH:                  | Data not available             |
| Melting Point:       | Data not available             |
| Boiling Point:       | Data not available             |
| Boiling Range:       | Data not available             |
| Flash Point:         | >200° C / >392° F (COC Method) |
| Evaporation Rate:    | Data not available             |
| Flammability:        | Data not available             |
| Flammability Limits: | Data not available             |
| Vapor Pressure:      | Data not available             |
| Vapor Density:       | Data not available             |
| Relative Density:    | 0.85 to 0.86                   |
| Solubilities:        | Insoluble in water             |



Page 6 of 8 -

11

## Lyden Fuel Force Power Steering Flush

SDS Number: FF350

Partition Coefficient: Auto-Ignition Temperature: Decomposition Temperature: Viscosity: Data not available Data not available Data not available >19.2 mm²/sec (kinematic at 40° C)

| 10                 | STABILITY AND REACTIVITY |  |
|--------------------|--------------------------|--|
| <u>Stability:</u>  |                          | Stable under normal conditions.            |
| <u>Reactivity:</u> |                          | Not reactive under normal conditions.      |
| Conditions to Av   | <u>oid:</u>              | No further relevant information available. |
| Hazardous React    | <u>tions:</u>            | No known hazardous reactions.              |
| Incompatible Ma    | aterials:                | Strong oxidizers.                          |
| Decomposition I    | Products:                | Oxides of carbon.                          |

#### TOXICOLOGICAL INFORMATION

| Routes of Exposure:   |   |
|-----------------------|---|
|                       | Inhalation, skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion. |
| Exposure Effects:     |   |
|                       | Repeated skin contact may cause dermatitis or an oil acne.  |
| Measures of Toxicity: |   |
|                       | -White mineral oil (petroleum):   |
|                       | LD50 Oral: (Rat) >5000 mg/kg  |



Page **7** of **8** –

## Lyden Fuel Force Power Steering Flush

SDS Number: FF350

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be mutagentic.

| 12 ECOLOGICA   | L INFORMATION  |  |
|--|--|--|
| Ecological Precautions:  |  | Do not allow product to reach ground water, water course or sewage system.               |
| <u>Ecological Effects:</u><br>No sp  | ecific environmental   | or aquatic data available.   |
| 13 DISPOSAL C  | ONSIDERATIONS  |  |
| Disposal Methods:  |  | Dispose of waste material in accordance with all local, state, and federal requirements. |
| Disposal Containers:   |  | Use properly approved container for disposal.  |
| Special Precautions:   |  | Do not flush to surface waters or drains.  |
| 14 TRANSPORT   | <b>INFORMATION</b>   |  |
| <u>UN Number:</u><br><u>UN Shipping Name:</u><br><u>Transport Hazard Class:</u><br><u>Packing Group:</u> | Data not available<br>Data not available<br>Data not available<br>Data not available |  |
| Environmental Hazards:   |  | Data not available   |
| Bulk Transport Guidance:   |  | Data not available   |
| Special Precautions:   |  | Not regulated by DOT.  |



Page 8 of 8 -

## Lyden Fuel Force Power Steering Flush

SDS Number: FF350

#### 15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

#### Last Revision Date: 03/06/2025

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. The supplier assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the supplier.