

Page 1 of 7 -

Lyden Fuel Force (H) Synthetic P/S Fluid & Conditioner (Honda/Acura)

SDS Number: FF385

PRODUCT AND COMPANY INFORMATION

<u>Product Name:</u> Lyden Fuel Force (H) Synthetic P/S Fluid & Conditioner (Honda/Acura)

Revision Date: 03/06/2025

SDS Number: FF385

<u>Common Name:</u> Hydrotreated heavy paraffinic power steering fluid

<u>CAS Number:</u> Blend <u>Product Code:</u> FF385

<u>Synonyms:</u> Power Steering Fluid

Company Identification:

Manufactured for: LYDEN OIL COMPANY 30692 Tracy Rd. Walbridge, OH 43462 www.lydenoil.com

For Product Information: 1-800-245-9336

For Emergencies: 1-800-424-9300 (CHEMTREC)

2 HAZARDS IDENTIFICATION

Signal Word: None

Hazard Classes/Categories:

None

Hazard Statement(s):

None

Precaution Statement(s):

P101: If medical advice is needed, have product container or label at

hand.

P102: Keep out of reach of children.

P103: Read label before use.



Page **2** of **7**

Lyden Fuel Force (H) Synthetic P/S Fluid & Conditioner (Honda/Acura)

SDS Number: FF385

Other Hazard Statement(s):

-NFPA Ratings: Health = 0 Fire = 1 Reactivity = 0

2

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	60-100

^{*}Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4 FIRST AID MEASURES

Description of First Aid Measures:

Inhalation:

Remove victim to fresh air and keep at rest in a position comfortable

for breathing. Get medical attention if symptoms occur.

Skin Contact:

Wash with soap and water. Remove contaminated clothing and wash

before reuse. Get medical attention if needed.

Eye Contact:

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Get medical attention if irritation occurs.

Ingestion:

Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by

medical personnel. Get medical attention if symptoms occur.



Page 3 of 7 -

Lyden Fuel Force (H) Synthetic P/S Fluid & Conditioner (Honda/Acura)

SDS Number: FF385

Symptoms and Effects, both acute and delayed:

No further relevent data available.

Recommended Actions:

Treat symptomatically. Call a doctor or poison

control center for guidance.

5 FIRE FIGHTING MEASURES

Recommended Fire-Extinguishing Equipment:

Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.

Possible Hazards During a Fire:

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Recommendations to Firefighters:

Proper protective equipment including breathing

apparatus.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Avoid eye contact. Avoid repeated or prolonged

skin contact.

Personal protective equipment must be worn. Avoid contact with skin, eyes or clothing.

Emergency Procedures:

Contain spilled material, collect in suitable and

properly labeled containers.



Page **4** of **7** -

Lyden Fuel Force (H) Synthetic P/S Fluid & Conditioner (Honda/Acura)

SDS Number: FF385

Environmental Precautions:

Do not allow product to reach sewage system or

any water course.

Inform respective authorities in case of seepage

into water course or sewage system.

Cleanup Procedures:

Absorb with liquid-binding material (sand,

diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

HANDLING AND STORAGE

Handling Precautions:

Wear personal protective equipment. Avoid contact

with eyes.

Storage Requirements:

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental

contamination.

EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

-64742-54-7 Distillates (petroleum), hydrotreated heavy parffinic (60-100%):

ACGIH TWA – 5mg/m³ (oil mist) ACGIH STEL - 10mg/m³ (oil mist) OSHA TWA – 5mg/m³ (oil mist)

Engineering Controls:

All ventilation should be designed in accordance

with OSHA standard (29 CFR 1910.94).



Page **5** of **7** -

Lyden Fuel Force (H) Synthetic P/S Fluid & Conditioner (Honda/Acura)

SDS Number: FF385

Personal Protective Equipment:

Wash hands before breaks and at the end of work. Use safety glasses and gloves.

PHYSICAL AND CHEMICAL PROPERTIES

Color: Clear
Physical State: Liquid
Odor: Petroleum

Odor Threshold:

pH:

Data not available

Melting Point:

Data not available

Boiling Point:

Data not available

Data not available

Data not available

Data not available

Flash Point: >200° C / >392° F (COC Method)

Evaporation Rate: Data not available Data not available Flammability: Data not available Flammability Limits: Vapor Pressure: Data not available Vapor Density: Data not available Relative Density: 0.84 to 0.865 Solubilities: Insoluble in water Partition Coefficient: Data not available Auto-Ignition Temperature: Data not available Decomposition Temperature: Data not available

Viscosity: >25 mm²/sec (kinematic at 40° C)

10 STABILITY AND REACTIVITY

Stability:

Stable under normal conditions.

Reactivity:

Not reactive under normal conditions.

Conditions to Avoid:

No further relevant information available.

Hazardous Reactions:

No known hazardous reactions.



Page **6** of **7** -

Lyden Fuel Force (H) Synthetic P/S Fluid & Conditioner (Honda/Acura)

SDS Number: FF385

Incompatible Materials:

Strong oxidizers.

Decomposition Products:

Oxides of carbon.

11 TOXICOLOGICAL INFORMATION

Routes of Exposure:

Inhalation, skin and eye contact are the primary routes of exposure although exposure may occur

following accidental ingestion.

Exposure Effects:

Repeated skin contact may cause dermatitis or an

oil acne.

Measures of Toxicity:

No test data available.

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be

mutagentic.

12 ECOLOGICAL INFORMATION

Ecological Precautions:

Do not allow product to reach ground water, water

course or sewage system.

Ecological Effects:

No specific environmental or aquatic data available.

13 DISPOSAL CONSIDERATIONS

Disposal Methods:

Dispose of waste material in accordance with all

local, state, and federal requirements.



Page **7** of **7** -

Lyden Fuel Force (H) Synthetic P/S Fluid & Conditioner (Honda/Acura)

SDS Number: FF385

Disposal Containers:

Use properly approved container for disposal.

Special Precautions:

Do not flush to surface waters or drains.

14 TRANSPORT INFORMATION

UN Number:Data not availableUN Shipping Name:Data not availableTransport Hazard Class:Data not availablePacking Group:Data not available

Environmental Hazards:

Data not available

Bulk Transport Guidance:

Data not available

Special Precautions:

Not regulated by DOT.

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16 OTHER INFORMATION

Last Revision Date: 03/06/2025

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. The supplier assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the supplier.



Page 1 of 8 -

Safety Data Sheet

Lyden Fuel Force Power Steering Flush

SDS Number: FF350

PRODUCT AND COMPANY INFORMATION

<u>Product Name:</u> Lyden Fuel Force Power Steering Flush

Revision Date: 03/06/2025 SDS Number: FF350

<u>Common Name:</u> Hydrotreated heavy paraffinic power steering flush

<u>CAS Number:</u> Blend <u>Product Code:</u> FF350

Synonyms: Power Steering Flush

Company Identification:

Manufactured for: LYDEN OIL COMPANY 30692 Tracy Rd. Walbridge, OH 43462 www.lydenoil.com

For Product Information: 1-800-245-9336

For Emergencies: 1-800-424-9300 (CHEMTREC)

HAZARDS IDENTIFICATION



Signal Word: DANGER

Hazard Classes/Categories:

Aspiration hazard, Category 1.

Hazard Statement(s):

H304: May be fatal if swallowed and enters airways.



Page 2 of 8 -

Lyden Fuel Force Power Steering Flush

SDS Number: FF350

Precaution Statement(s):

P101: If medical advice is needed, have product container or label at

hand.

P102: Keep out of reach of children.

P103: Read label before use.

P301+310: IF SWALLOWED: Immediately call a POISON

CENTER/doctor

P331: Do NOT induce vomiting.

P405: Store locked up.

P501: Dispose of contents/container in accordance with

local/regional/national/international regulation.

Other Hazard Statement(s):

-NFPA Ratings:

Health = 0

Fire = 1

Reactivity = 0

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	60-100
White mineral oil (petroleum)	8042-47-5	1-5

^{*}Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4 FIRST AID MEASURES

Description of First Aid Measures:

Inhalation:

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately.



Page 3 of 8 -

Safety Data Sheet

Lyden Fuel Force Power Steering Flush

SDS Number: FF350

Skin Contact:

Wash with soap and water. Remove contaminated clothing and wash

before reuse. Get medical attention if needed.

Eye Contact:

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Get medical attention if irritation occurs.

Ingestion:

Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

Symptoms and Effects, both acute and delayed:

Ingestion: Adverse symptoms may include the

following: nausea or vomiting.

Recommended Actions:

Treat symptomatically. Call a doctor or poison

control center for guidance.

FIRE FIGHTING MEASURES

Recommended Fire-Extinguishing Equipment:

Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.

Possible Hazards During a Fire:

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.



Page 4 of 8 -

Safety Data Sheet

Lyden Fuel Force Power Steering Flush

SDS Number: FF350

Recommendations to Firefighters:

Proper protective equipment including breathing

apparatus.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Avoid eye contact. Avoid repeated or prolonged

skin contact.

Personal protective equipment must be worn. Avoid contact with skin, eyes or clothing.

Emergency Procedures:

Contain spilled material, collect in suitable and

properly labeled containers.

Environmental Precautions:

Do not allow product to reach sewage system or

any water course.

Inform respective authorities in case of seepage

into water course or sewage system.

Cleanup Procedures:

Absorb with liquid-binding material (sand,

diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

HANDLING AND STORAGE

Handling Precautions:

Wear personal protective equipment. Avoid contact

with eyes.

Storage Requirements:

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be



Page **5** of **8** -

Safety Data Sheet

Lyden Fuel Force Power Steering Flush

SDS Number: FF350

carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

-64742-54-7 Distillates (petroleum), hydrotreated heavy parffinic (60-100%):

ACGIH TWA – 5mg/m³ (oil mist) ACGIH STEL - 10mg/m³ (oil mist) OSHA TWA – 5mg/m³ (oil mist)

Engineering Controls:

All ventilation should be designed in accordance

with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work.

Use safety glasses and gloves.

9 PHYSICAL AND CHEMICAL PROPERTIES

Color: Clear
Physical State: Liquid
Odor: Petroleum

Odor Threshold:

pH:

Data not available

Data not available

Melting Point:

Data not available

Boiling Point:

Data not available

Data not available

Data not available

Flash Point: >200° C / >392° F (COC Method)

Evaporation Rate:

Flammability:

Data not available

Flammability Limits:

Data not available

Vapor Pressure:

Data not available

Vapor Density:

Data not available

Oata not available

Oata not available

Data not available

Insoluble in water



Page **6** of **8** -

Lyden Fuel Force Power Steering Flush

SDS Number: FF350

Partition Coefficient:

Auto-Ignition Temperature:

Data not available

Decomposition Temperature:

Data not available

Viscosity: >19.2 mm²/sec (kinematic at 40° C)

10 STABILITY AND REACTIVITY

Stability:

Stable under normal conditions.

Reactivity:

Not reactive under normal conditions.

Conditions to Avoid:

No further relevant information available.

Hazardous Reactions:

No known hazardous reactions.

Incompatible Materials:

Strong oxidizers.

Decomposition Products:

Oxides of carbon.

11 TOXICOLOGICAL INFORMATION

Routes of Exposure:

Inhalation, skin and eye contact are the primary routes of exposure although exposure may occur

following accidental ingestion.

Exposure Effects:

Repeated skin contact may cause dermatitis or an

oil acne.

Measures of Toxicity:

-White mineral oil (petroleum):

LD50 Oral: (Rat) >5000 mg/kg



Page **7** of **8** —

Lyden Fuel Force Power Steering Flush

SDS Number: FF350

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be

mutagentic.

12 ECOLOGICAL INFORMATION

Ecological Precautions:

Do not allow product to reach ground water, water

course or sewage system.

Ecological Effects:

No specific environmental or aquatic data available.

13 DISPOSAL CONSIDERATIONS

Disposal Methods:

Dispose of waste material in accordance with all

local, state, and federal requirements.

Disposal Containers:

Use properly approved container for disposal.

Special Precautions:

Do not flush to surface waters or drains.

14 TRANSPORT INFORMATION

UN Number:Data not availableUN Shipping Name:Data not availableTransport Hazard Class:Data not availablePacking Group:Data not available

Environmental Hazards:

Data not available

Bulk Transport Guidance:

Data not available

Special Precautions:

Not regulated by DOT.



Page 8 of 8 -

Lyden Fuel Force Power Steering Flush

SDS Number: FF350

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16 OTHER INFORMATION

Last Revision Date: 03/06/2025

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. The supplier assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the supplier.