

Page **1** of **8** -

1

Lyden Fuel Force 75W-90 Synthetic Gear Lube

SDS Number: FF595

PRODUCT AND COMPANY INFORMATION

Product Name:	Lyden Fuel Force 75W-90 Synthetic Gear Lube
Revision Date:	03/07/2025
SDS Number:	FF595
Common Name:	75W-90 Synthetic Gear Oil
CAS Number:	Blend
Product Code:	FF595
Synonyms:	75W-90 Gear Oil

Company Identification:

Manufactured for: LYDEN OIL COMPANY 30692 Tracy Rd. Walbridge, OH 43462 www.lydenoil.com

For Product Information:	1-800-245-9336
For Emergencies:	1-800-424-9300 (CHEMTREC)

HAZARDS IDENTIFICATION



Signal Word:

2

Hazard Classes/Categories:

Skin sensitization, Category 1. Hazardous to the aquatic environment, Category acute 3. Hazardous to the aquatic environment, Category chronic 3.

WARNING



Page **2** of **8** –

SDS Number: FF595

Lyden Fuel Force 75W-90 Synthetic Gear Lube

5B5 Namber: 11555	
Hazard Statement(s):	H317: May cause an allergic skin reaction. H412: Harmful to aquatic life with long-lasting effects.
	H412. Harmul to aquatic life with long-lasting effects.
Precaution Statement(s):	
	P101: If medical advice is needed, have product container or label at hand.
	P102: Keep out of reach of children.
	P102: Read label before use.
	P280: Wear protective gloves.
	P273: Avoid release to the environment.
	P261: Avoid breathing vapors/spray.
	P272: Contaminated work clothing should not be allowed out of the workplace.
	P302+352: IF ON SKIN: Wash with plenty of water.
	P363: Wash contaminated clothing before reuse.
	P333+313: If skin irritation or a rash occurs: Get medical
	advice/attention.
	P501: Dispose of contents/container in accordance with
	local/regional/national/international regulation.
Other Hazard Statement(s):	
<u>other Hazara otatement(oji</u>	-NFPA Ratings:
	Health = 1
	Fire = 1
	Reactivity = 0
	incactivity - 0

3

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Alkyl methacrylate mixture	Proprietary	1 - 5
Long-chain alkyl amine	N/A	0.1 - 1
Long-chain alkenyl amine	N/A	0.1 - 1

*Any concentration shown as a range is to protect confidentiality or is due to batch variation.



Page 3 of 8 -

4

Lyden Fuel Force 75W-90 Synthetic Gear Lube

SDS Number: FF595

FIRST AID MEASURES

Description of First Aid Measures:

Inhalation:	
	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately.
Skin Contact:	
	Wash with plenty of soap and water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Eye Contact:	
	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Continue to rinse for at least 20 minutes. Get medical attention if irritation occurs.
Ingestion:	
	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

Symptoms and Effects, both acute and delayed:

No further relevent data available.

Recommended Actions:

Treat symptomatically. Call a doctor or poison control center for guidance.



Page 4 of 8 -

Lyden Fuel Force 75W-90 Synthetic Gear Lube

SDS Number: FF595

5 FIRE FIGHTING MEASURES	
Recommended Fire-Extinguishing Equipment:	Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.
Possible Hazards During a Fire:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
Recommendations to Firefighters:	Proper protective equipment including breathing apparatus.
6 ACCIDENTAL RELEASE MEASU	JRES
Personal Precautions:	Avoid eye contact. Avoid repeated or prolonged skin contact. Personal protective equipment must be worn. Avoid contact with skin, eyes or clothing.
Emergency Procedures:	Contain spilled material, collect in suitable and properly labeled containers.
Environmental Precautions:	Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.
<u>Cleanup Procedures:</u>	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.



Page **5** of **8** -

Lyden Fuel Force 75W-90 Synthetic Gear Lube

SDS Number: FF595

7 HANDLING AND STORAGE Handling Precautions: Wear personal protective equipment. Avoid contact with eyes. Storage Requirements: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

8

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work. Use safety glasses and gloves.

9

PHYSICAL AND CHEMICAL PROPERTIES

Color: Physical State: Odor: Odor Threshold: pH: Melting Point: Yellow Liquid Petroleum Data not available Data not available Data not available



Page 6 of 8 -

Lyden Fuel Force 75W-90 Synthetic Gear Lube

SDS Number: FF595

Boiling Point:	Data not available
Boiling Range:	Data not available
Flash Point:	185° C / 365° F (COC Method)
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	0.865 to 0.875
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	>80 mm ² /sec (kinematic at 40° C)

TABILITY AND REACTIVITY	
	Stable under normal conditions.
	Not reactive under normal conditions.
<u>d:</u>	No further relevant information available.
<u>ns:</u>	No known hazardous reactions.
erials:	Strong oxidizers.
oducts:	Oxides of carbon.
OXICOLOGICAL INFORMATION	J
	<u>d:</u> ns: erials: educts:

Routes of Exposure:

Inhalation, skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.



Page 7 of 8 -

Safety Data Sheet

SDS Number: FF595	
Exposure Effects:	Repeated skin contact may cause dermatitis or an oil acne.
Measures of Toxicity:	No test data available.
Carcinogenic/Mutagenic Precautions:	Non-carcinogenic and not expected to be mutagentic.
12 ECOLOGICAL INFORMATION	
Ecological Precautions:	Do not allow product to reach ground water, water course or sewage system.
<u>Ecological Effects:</u> No specific environmenta	al or aquatic data available.
13 DISPOSAL CONSIDERATIONS	
Disposal Methods:	Dispose of waste material in accordance with all local, state, and federal requirements.
Disposal Containers:	Use properly approved container for disposal.
Special Precautions:	Do not flush to surface waters or drains.

TRANSPORT INFORMATION

UN Number:Data not availableUN Shipping Name:Data not availableTransport Hazard Class:Data not availablePacking Group:Data not available

14



Page 8 of 8 -

Safety Data Sheet

	Lyden Fuel Force 75W-90 Synthetic Gear Lube
SDS Number: FF595	
Environmental Hazards:	Data not available
Bulk Transport Guidance:	Data not available
Special Precautions:	Not regulated by DOT.
15 REGULATORY INFORMATION	
This material and all of its components are listed of Substances Control Act.	on the Inventory of Existing Chemical Substances under the Toxic

16	OTHER INFORMATION

Last Revision Date: 03/07/2025

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. The supplier assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the supplier.