



# Safety Data Sheet

Page 1 of 8

## Lyden Fuel Force Transmission Cleaner

SDS Number: FF840

### 1 PRODUCT AND COMPANY INFORMATION

Product Name: Lyden Fuel Force Transmission Cleaner  
Revision Date: 03/06/2025  
SDS Number: FF840  
Common Name: N/A  
CAS Number: Blend  
Product Code: FF840  
Synonyms: N/A

#### Company Identification:

*Manufactured for:*  
LYDEN OIL COMPANY  
30692 Tracy Rd.  
Walbridge, OH 43462  
[www.lydenoil.com](http://www.lydenoil.com)

For Product Information: 1-800-245-9336  
For Emergencies: 1-800-424-9300 (CHEMTREC)

### 2 HAZARDS IDENTIFICATION

Signal Word: **None**

Hazard Classes/Categories: None

Hazard Statement(s): None

Precaution Statement(s):  
P101: If medical advice is needed, have product container or label at hand.  
P102: Keep out of reach of children.  
P103: Read label before use.



# Safety Data Sheet

Page 2 of 8

## Lyden Fuel Force Transmission Cleaner

SDS Number: FF840

Other Hazard Statement(s):

-NFPA Ratings:

Health = 0

Fire = 1

Reactivity = 0

### 3 COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

*Mixture of the substances listed below with nonhazardous additions.*

Chemical Name	CAS Number	Percentage
White mineral oil (petroleum)	8042-47-5	5-10

*\*Any concentration shown as a range is to protect confidentiality or is due to batch variation.*

### 4 FIRST AID MEASURES

Description of First Aid Measures:

Inhalation:

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.

Skin Contact:

Flush contaminated skin with plenty of water. Get medical attention if symptoms occur.

Eye Contact:

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Get medical attention if irritation occurs.

Ingestion:

Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.



# Safety Data Sheet

Page 3 of 8

## Lyden Fuel Force Transmission Cleaner

SDS Number: FF840

Symptoms and Effects, both acute and delayed:

No further relevant data available.

Recommended Actions:

Treat symptomatically. Call a doctor or poison control center for guidance.

### 5 FIRE FIGHTING MEASURES

Recommended Fire-Extinguishing Equipment:

Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.

Possible Hazards During a Fire:

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Recommendations to Firefighters:

Proper protective equipment including breathing apparatus.

### 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Avoid eye contact. Avoid repeated or prolonged skin contact.  
Personal protective equipment must be worn.  
Avoid contact with skin, eyes or clothing.

Emergency Procedures:

Contain spilled material, collect in suitable and properly labeled containers.



# Safety Data Sheet

Page 4 of 8

## Lyden Fuel Force Transmission Cleaner

SDS Number: FF840

### Environmental Precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

### Cleanup Procedures:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

## 7 HANDLING AND STORAGE

### Handling Precautions:

Wear personal protective equipment. Avoid contact with eyes.

### Storage Requirements:

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Limits:

-White mineral oil (petroleum):

ACGIH TLV (United States, 6/2013)

TWA: 5 mg/m<sup>3</sup> 8 hours. Form: Inhalable fraction

NIOSH REL (United States, 4/2013)

TWA: 5 mg/m<sup>3</sup> 10 hours. Form: Mist

STEL: 10 mg/m<sup>3</sup> 15 minutes. Form: Mist



# Safety Data Sheet

Page 5 of 8

## Lyden Fuel Force Transmission Cleaner

SDS Number: FF840

OSHA PEL (United States, 2/2013)  
TWA: 5 mg/m<sup>3</sup> 8 hours

### Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

### Personal Protective Equipment:

Wash hands before breaks and at the end of work.  
Use safety glasses and gloves.

<b>9</b>	<b>PHYSICAL AND CHEMICAL PROPERTIES</b>
----------	---

Color:	Red
Physical State:	Liquid
Odor:	Petroleum
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	Data not available
Boiling Range:	Data not available
Flash Point:	180° C / 356° F (COC Method)
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	0.855 to 0.865
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	>28.5 mm <sup>2</sup> /sec (kinematic at 40° C)



# Safety Data Sheet

Page 6 of 8

## Lyden Fuel Force Transmission Cleaner

SDS Number: FF840

### 10 STABILITY AND REACTIVITY

Stability:

Stable under normal conditions.

Reactivity:

Not reactive under normal conditions.

Conditions to Avoid:

No further relevant information available.

Hazardous Reactions:

No known hazardous reactions.

Incompatible Materials:

Strong oxidizers.

Decomposition Products:

Oxides of carbon.

### 11 TOXICOLOGICAL INFORMATION

Routes of Exposure:

Inhalation, skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Exposure Effects:

Repeated skin contact may cause dermatitis or an oil acne.

Measures of Toxicity:

-White mineral oil (petroleum):

LD50 Oral (Rat): >5000 mg/kg

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be mutagenic.



# Safety Data Sheet

## Lyden Fuel Force Transmission Cleaner

SDS Number: FF840

### 12 ECOLOGICAL INFORMATION

Ecological Precautions:

Do not allow product to reach ground water, water course or sewage system.

Ecological Effects:

No specific environmental or aquatic data available.

### 13 DISPOSAL CONSIDERATIONS

Disposal Methods:

Dispose of waste material in accordance with all local, state, and federal requirements.

Disposal Containers:

Use properly approved container for disposal.

Special Precautions:

Do not flush to surface waters or drains.

### 14 TRANSPORT INFORMATION

UN Number: Data not available

UN Shipping Name: Data not available

Transport Hazard Class: Data not available

Packing Group: Data not available

Environmental Hazards:

Data not available

Bulk Transport Guidance:

Data not available

Special Precautions:

Not regulated by DOT.

### 15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.



# Safety Data Sheet

Page 8 of 8

Lyden Fuel Force Transmission Cleaner

SDS Number: FF840

16

## OTHER INFORMATION

Last Revision Date: 03/06/2025

*The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. The supplier assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the supplier.*